

5mW 405nm Line Laser Module

VM-0405F-005M-GL-0A0

Features

- Uniform and detail-oriented
- No stripes & No noise
- Compact, small size
- Low thermal resistance
- High power conversion efficiency

Applications

- 3D measurement
- medical lighting
- Indication and positioning



Description

This product VM-0405F-050M-GL-0A0 is integrated by in-house manufactured & high-quality laser diode and is shielding with copper for better heat dissipation. Compared with traditional laser and LED, it enables to provide a higher peak power and lower power consumption, low wavelength drift with temperature and good reliability. It provides narrower emission angle without optical and thermal compensation, which allow to operate a wider range of environments. This product with laser diodes with small-sized, light, low price, long life, low power consumption and fast frequency response. It can be applied to infrastructure alignment, positioning, indication, inspection, machine vision and other fields for ideal invisible laser source.


PRODUCT IDENTIFY

Part Number	Description
VM-0405F-005M-GL-0A0	5mW 405nm Line Shape Laser module

CODE RULES

VM- 0405F-005M -G L - 0 A 0

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩




Annex, option=0
 Product version, A
 Accessories 0 = standard
 Shape, L= Line
 Angle, G = 110-140 degree
 Units, M =milliwatt
 Power value, 5
 Laser class: F=Class 1
 Wavelength, 405nm
 Product classification, **VCSEL Module**

I. Specifications

Parameters	Typical values	Unit	Remarks
Lifetime	8000	H	-
Wavelength	405±10	nm	-
Optical power	5±1	mW	-
Rated current	<45	mA	-
Power consumption	<250	mW	-
Beam line width	Spring insert, customizable	mm	-
Beam line width	0.5	mm	@30mm
Beam emission angle	2	mard	-
Beam divergence	110	°	-
Operating voltage	DC 5.0-5.8	V	-
Storage temperature	-40 to +80	°C	-
Operating temperature	-20 to +60	°C	-
Dimensions	Φ7×L13.7	mm	See Mechanics
Beam spot	Line	-	-
Positive electrical color	Red	-	-
Negative electrical color	Black	-	-
Laser classification	Class 1	-	-
Weight	2.0	g	Customizable

Note: Electro-Optical Characteristic with a package or diffuser would require further evaluation. Values are based on limited sample size and estimated values.

II. Mechanic schematic



III. Laser Product Safety

The output power of this module is classified as class 1, one can refer to IEC 60825-1:2014 《Laser Product Safety: Part 1: Devices classification, requirements and user's Manual》.

IV. Copyright Statement

This documentation is wholly owned by Brightlaser Ltd. Any one, any organization or third part may not partly or wholly copy, reproach the documentation. Otherwise, anyone can be prosecuted.

V. Revision History

Revisions	Date	Description
V.01	2021/12/01	The first official Version